

Таблица максимально допустимых оборотов подвесных и стационарных двигателей

Evinrude RPM Chart		
HP/Model	WOT RPM	Gear Ratio
5 4-Stroke	5500-6500	2.23
6 4-Stroke	5500-6500	2.23
8 4-Stroke	5000-6000	2.42
9.9 4-Stroke	5000-6000	2.42
9.9 HT 4-Stroke	4000-5000	2.42
15 4-Stroke	5000-6000	2.42
25 4-Stroke	4700-5300	2.09
30 4-Stroke	5200-5800	2.09
40 4-Stroke	5200-5800	2.27
50 4-Stroke	5900-6500	2.27
65 Commercial	5500-6000	2.67
70 4-Stroke	5200-5800	2.42
75 Ficht	4750-5250	2
90 Commercial	4500-5500	2
90 Ficht	5250-5750	2
115 Ficht	5250-5750	2
135 Ficht	4750-5250	1.86
150 Ficht	4750-5250	1.86
175 Ficht	5250-5750	1.86
200 Ficht	5500-6000	1.86
225 Ficht	5500-6000	1.86
225 Ficht HO	5500-6000	1.86
250 Ficht	5500-6000	1.86
250 H.O.	4500-6000	1.71
250 V6	4500-5800	1.85

Evinrude E-tec RPM Chart	
HP/Model	WOT RPM
40	5500-6000

Johnson RPM Chart		
HP/Model	WOT RPM	Gear Ratio
2	4000-5000	1.85
3.3	4500-5500	1.85
3.5	4500-5500	1.85
4	4500-5500	2.08
4 4-Stroke	4000-5000	1.92
5	4600-5400	1.92
6	4500-5500	2.23
6 4-Stroke	5500-6500	2.23
8	5000-6000	2.23
8 4-Stroke	5000-6000	2.42
9.9	5000-6000	2.23
9.9 4-Stroke	4500-5500	1.92
15	5000-6000	2.23
15 4-Stroke	5400-6000	1.92
25	4500-5500	2.15
25	5200-5800	2.15
25 4-Stroke	5000-5600	2.09
30	5200-5800	2.15
30 4-Stroke	5500-6100	2.09
35	5200-5800	2.15
40	4500-5500	2.23
40 4-Stroke	5200-5800	2.27
50	4500-5500	2.23
50 4-Stroke	5900-6500	2.27
60	5000-6000	2.23
60 4-Stroke	4700-5300	2.42
70	5000-6000	2.23
70 4-Stroke	5200-5800	2.42
90	4500-5500	2

Mercury RPM Chart		
HP/Model	WOT RPM	Gear Ratio
2.5	4000-5000	1.85
2.5 4-Stroke	5000-6000	2.15
3.3	4500-5500	2.15
3.5 4-Stroke	5000-6000	2.15
4	4500-5500	2.15
4 4-Stroke	4500-5500	2.15
5	4000-5000	2.15
5 4-Stroke	4500-5500	2.15
6	4000-5000	2
6 4-Stroke	5000-6000	2.15
8	4500-5500	2
8 4-Stroke	5000-6000	2.08
9.9	5000-6000	2
9.9 4-Stroke	4500-5500	2.01
9.9 Big Foot	4500-5500	2.42
9.9 Prokicker 4-Stroke	5000-6000	2.42
9.9 Saltwater	4500-5500	2.42
15	5000-6000	2
15 4-Stroke	4500-5500	2
15 Big Foot	4500-5500	2.42
20	4500-5500	2.25
20 4-Stroke	5400-6100	2.15
25 Classic	5000-6000	2.25
25 Big Foot	5500-6000	2.4
25 EFI 4-Stroke Jet Drive	5000-5500	
25 EFI 4-Stroke	5000-6000	1.92
30	4500-5500	2
30 4-Stroke	5500-6000	2

50	5500-6000
60	5500-6000
75	4500-5500
90	4500-5500
115	5500-6000
130	5000-6000
150	4850-5850
150 H.O.	4850-5850
175	4850-5850
200	4750-5750
200 H.O.	4500-5800
200	4850-5850
225	4500-5800
225 H.O.	4500-5800

HONDA RPM CHART		
HP/Model	WOT RPM	Gear Ratio
2	4000-5000	2.4
5	4000-5000	2.1
8	4950-5500	2.4
9.9	4500-5500	2.1
15	5000-6200	2.1
20 4-Stroke	5000-6000	2.08
25	5000-6000	2.08
30	5500-6000	2.08
35 4-Stroke	5500-6000	
40	5000-6000	2.09
50	5500-6000	2.09
65 4-Stroke	5000-6000	
75	5000-6000	2.3
90	5000-6000	2
105 4-Stroke	5000-6000	
115	5000-6000	2

90 4-Stroke	4500-5500	2.59
90 OP	4500-5500	2
115	4500-5500	2
115 4-Stroke	5000-6000	2.59
115 OP	4500-5500	2
135	5000-6000	2.25
135 OP	5000-6000	2.25
140 4-Stroke	5600-6200	2.38
150	4500-5500	1.86
150 OP	4500-5500	1.86
175	4500-5500	1.86
175 OP	4500-5500	1.86
200	5000-6000	1.86
200 4-Stroke	5000-6000	2.29
200 OP	5000-6000	1.86
225	5000-6000	1.86
225 4-Stroke	5000-6000	2.29
225 OP	5000-6000	1.86
225 HO	5000-6000	1.86
250 OP	5000-6000	1.86

MERCUISER RPM CHART		
HP/Model	WOT RPM	Gear Ratio
3.0 L 135	4400-4800	2.00 A1
4.3 L 190	4400-4800	1.81 A1
4.3 LH 205	4400-4800	1.62 A1
4.3 LEFI 210	4400-4800	1.62 A1
4.3 L MPI 220 HP	4400-4800	1.62 A1
5.0 L 220	4400-4800	1.62 A1
5.0 L 220	4400-4800	1.65 B1
5.0 LEFI 240	4400-4800	1.47 A1
5.0 LEFI 240	4400-4800	1.65 B1
5.0 L MPI 260 HP	4600-5000	1.62 A1

30 EFI 4-Stroke	5200-6200	1.92
40 Classic	4500-5500	2
40	5000-5500	1.83
40 4-Stroke	5500-6000	2
40 Big Foot	5500-6000	2.3
40 EFI 4-Stroke	5000-5500	
50 Classic	5000-5500	1.83
50 4-Stroke	5500-6000	1.83
50 Big Foot	5500-6000	2.3
50 EFI Big Foot 4-Stroke	5500-6000	2.33
60 Classic	5000-5500	1.64
60 Big Foot	5000-5500	2.3
60 4-Stroke	5500-6000	1.83
60 EFI Big Foot 4-Stroke	5500-6000	2.33
75 Classic	4750-5250	2.3
75 4-Stroke	5000-6000	2.3
75 EFI 4-Stroke	5000-6000	2.33
75 OptiMax	5000-5750	2.33
90 Classic	5000-5500	2.3
90 SW	5000-5500	2.3
90 4-Stroke	5000-6000	2.3
90 4-Stroke SW	5000-6000	2.3
90 OptiMax	5000-5750	2.33
90 EFI 4-Stroke	5000-6000	2.33
115	4750-5250	2.07
115 4-Stroke	5000-6000	2.07
115 4-Stroke SW	5000-6000	2.07
115 EFI 4-Stroke	5800-6400	2.07
115 OptiMax	5000-5700	2.07
125 Classic	4750-5250	2.07
125 SW	4750-5250	2.07
135 OptiMax	5000-5600	2

130	5000-6000	2
150 4-Stroke Inline	5000-6000	2.14
200	5000-6000	1.86
225	5000-6000	1.86

MERCURY VERADO RPM CHART		
HP/Model	WOT RPM	Gear Ratio
135	5200-6400	2.08
150	5800-6400	2.08
175	5800-6400	2.08
200	5800-6400	2.08
225	5800-6400	1.85
250	5800-6400	1.85
275	5800-6400	1.85

NISSAN/TOHATSU RPM CHART		
HP/Model	WOT RPM	Gear Ratio
2.5	3800-5200	1.85
2.5 4-Stroke	4500-5500	2.15
3.5	5000-6000	2.15
4 4-Stroke	4500-5500	2.15
5	4500-5500	2.15
5 4-Stroke	4500-5500	2.15
6 4-Stroke	5000-6000	2.15
8	4500-5500	2.08
8 4-Stroke	5000-6000	2.08
9.8	5000-5800	2.08
9.8 4-Stroke	5000-6000	2.08
9.9 4-Stroke	4500-5500	2.08
15 4-Stroke	5000-6000	1.85
15 4-Stroke	5000-6000	2.15
18	4750-5500	1.85

5.0 L MPI 260 HP	4600-5000	1.50 B1
5.7 L 250	4400-4800	1.47 A1
5.7 L 250	4400-4800	1.65 B1
5.7LEFI 260	4400-4800	1.47 A1
5.7LEFI 260	4400-4800	1.65 B1
350 Mag MPI 300	4800-5200	1.47 A1
350 Mag MPI 300	4800-5200	1.50 B1
350 Mag MPI Horizon 300 HP	4800-5200	1.5 B1
350 Horizon 300	4600-5000	1.47 A1
350 Horizon 300	4600-5000	1.50 B1
MX 6.2 L MPI 320	4800-5200	1.65 B1
496 Mag 375	4400-4800	1.5 B1
496 Mag HO 425	4600-5000	1.5 B1

YAMAHA RPM CHART		
HP/Model	WOT RPM	Gear Ratio
2	4000-5000	2.08
3	4500-5500	2.08
4 4-Stroke	4000-5000	2.08
5	4500-5500	2.08
6 4-Stroke	4500-5500	2.08
8	4500-5500	2.08
8 4-Stroke	5000-6000	2.08
8 4-Stroke HT	5000-6000	2.92
9.9	4500-5500	2.08
9.9 4-Stroke	4500-5500	2.92
9.9 4-Stroke HT	4000-5000	2.92
15	4500-5500	2.08
15 4-Stroke	4500-5500	2.08
25	4500-5500	2.08
25	4500-5500	1.85

135 SW OptiMax	5000-5600	2
150 XR6	5000-5600	1.87
150 SW	5000-5600	1.87
150 EFI	5000-5600	1.87
150 SW EFI	5000-5600	1.87
150 OptiMax	5250-5750	1.87
175 EFI	5000-5600	1.87
175 OptiMax	5250-5750	1.87
175 OptiMax Pro XS	5500-6000	1.87
200 Classic	5000-5600	1.87
200 SW	5000-5600	1.87
200 EFI	5000-5800	1.87
200 EFI SW	5000-5600	1.87
200 OptiMax	5000-5750	1.75
225 EFI	5000-5800	1.75
225 EFI SW	5000-5500	1.75
225 OptiMax	5000-5750	1.75
225 OptiMax Pro XS	5500-6000	1.75
225 XL OptiMax SW	5000-5750	1.75
250 XL EFI SW	5000-5800	1.75
250 OptiMax	5500-6000	1.75
250 OptiMax Pro XS	5500-6000	1.75
300 Verado	5800-6400	1.75

Volvo RPM Chart		
HP/Model	WOT RPM	Gear Ratio
3.0 GL	4200-4600	1.85
3.0 GS	4200-4600	1.97
3.0 GS	4200-4600	2.18
3.0 GS	4400-4800	1.85
4.3 GL	4400-4800	1.66
4.3 GL	4200-4600	1.79

20 4-Stroke	5400-6100	2.15
25	4800-5500	1.92
25 4-Stroke	5000-6000	1.92
30	4800-5500	1.92
30 4-Stroke	5250-6250	1.92
40	4500-5500	1.85
40 TLDI	5150-5850	1.85
50	5000-5700	1.85
50 Orbital	5000-5700	1.85
50 TLDI	5150-5850	1.85
70	4900-5600	2.3
70 TLDI	5150-5850	2.3
90	5000-5500	2.3
90 TLDI	5150-5850	2
115	5200-5700	2
115 TLDI	5150-5850	2
120	5200-5700	2
140	5200-5700	2

SUZUKI RPM CHART		
HP/Model	WOT RPM	Gear Ratio
5	4500-5400	1.91
6	4500-5500	1.91
DF9.9	4500-5500	1.91
DF15	5400-6000	1.91
DT25	4500-5500	1.91
DF25	4700-5300	2.09
DF30	5500-6100	2.09
DF40	5200-5800	2.09
DF50	5500-6500	2.09
DF60	4700-5300	2.42
DF70	5200-5800	2.42
DT85	5000-5600	2.08

25 4-Stroke	5500-6000	2.08
25 4-Stroke HT	5000-6000	2.41
30	4500-5500	1.85
30 4-Stroke	5000-6000	2
40	4500-5500	1.85
C40	4500-5500	1.85
F40 4-Stroke	5000-6000	2
50	4500-5500	1.85
C50	4500-5500	1.85
F50 4-Stroke	5000-6000	1.85
T50 HT	5000-6000	2.33
60	4500-5500	2.33
C60	4500-5500	2.33
70	5000-6000	2.33
C70	5000-6000	2.33
F80 4-Stroke	5000-6000	2.31
90	4500-5500	2
F90	4500-5500	2
F100 4-Stroke	5000-6000	2.31
115	4500-5500	2
F115 4-Stroke	5000-6000	2.15
130	5000-6000	2
150 SW EFI	4500-5500	1.86
150 HPDI	4500-5500	1.86
F150 4-Stroke	5000-6000	2
V Max 150 HPDI	4500-5500	2
V Max 150 TRP	4500-5500	2
V Max 150	4500-5500	2
V Max 150 EFI	4500-5500	2
175 HPDI	4500-5500	1.86
V Max 175	4500-5500	1.86
V Max 175 HPDI	4500-6000	1.86
200 SW EFI	4500-5500	1.86

4.3 GL	4200-4600	1.85
4.3 GL	4200-4600	1.89
4.3 Gi	4400-4800	1.85
4.3 Gi	4400-4800	1.79
4.3 Gi	4400-4800	1.66
4.3 GS	4400-4800	1.66
4.3 GS	4400-4800	1.79
4.3 GS	4400-4800	1.85
5.0 FL	4200-4600	1.6
5.0 Fi	4200-4800	1.6
5.0 Fi	4200-4800	1.66
5.0 GL	4400-4800	1.51
5.0 GL	4400-4800	1.6
5.0 Gi	4600-5000	1.51
5.0 Gi	4600-5000	1.6
5.7 Gi	4200-4600	1.51
5.7 GL	4200-4600	1.6
5.7 GS	4400-4800	1.43
5.7 GS	4200-4600	1.51
5.7 GS	4400-4800	1.51
5.7 Gsi	4600-5100	1.51
5.7 Gsi	4600-5000	1.43
5.8 FL	4000-4400	1.51
5.8 Fi	4200-4600	1.51
5.8 Fsi	4600-5000	1.51
7.4 GL	4200-4600	1.43
7.4 Gi	4200-4600	1.43

DF90	4500-5500	2.59
DT100	5250-5750	2.08
115 EFI	5500-6000	2.08
DF115	5000-6000	2.59
140 EFI	5250-5750	2.08
DF 140	5600-6200	2.59
150 EFI	5200-6000	1.86
DF 150	5000-6000	2.5
DF 175	5500-6100	2.5
DF 200	5000-6000	2.29
225 EFI	5000-5600	1.86
DF 225	5000-6000	2.29
DF 250	5500-6100	2.29
DF250 SS	5300-6300	2.08
DF300	5700-6300	2.08

200 HPDI	4500-5500	1.86
F200 4-Stroke V6	5000-6000	2
V Max 200 HPDI	4500-5500	1.86
V Max 200 3.1 EFI	4500-5500	1.81
V Max 200 3.3 HPDI Series 2	5000-6000	1.81
225 SW EFI	4500-5500	1.81
F225 4-Stroke V6	5000-6000	2
V Max 225 3.1 EFI	4500-5500	1.81
V Max 225 3.3 HPDI Series 2	5000-6000	1.75
1 V Max 250 3.1	4500-5500	1.81
V Max 250 3.3 HPDI Series 2	5000-6000	1.75
250 SW EFI	4500-5500	1.81
F250 4-Stroke V6	5000-6000	2
F300 4-Stroke V8 5.3L	5000-6000	1.73
V Max 300 3.3 HPDI Series 2	4500-6000	1.75
F350 4-Stroke V8 5.3L	5000-6000	1.73